



TRANSMIT VIDEO OVER UTP

Using the different combinations of the Quaddrix Smart Cabling products you can transmit video signals over UTP cable to distances from 250m to 1500m

	QT-TXRX-P	QT-TX-P	QT-TX-A	QT-RX-A
Max. Distance	Up to 250mts (using a pair)	Up to 800mts (combined with QTRX-A)	Up to 1500mts (combined with QTRX-A)	Up to 1500mts (combined with QT-TX-A)
Power Supply	Not Required	Not Required	12V DC / 24V AC	12V DC / 24V AC
Power Consumption	-	-	0.5W	0.5W
Normal Output Level	1.0 p-p 75 Ω	1.0 p-p 75 Ω	1.0 p-p 75 Ω	1.0 p-p 75 Ω
Bandwidth	DC~6Mhz	DC~6Mhz	DC~6Mhz	DC~6Mhz
Differential Gain	<2%	<2%	<2%	<2%
S/N Ratio	60dB	60dB	60dB	60dB
Op. Temperature	-25°~70° C	-25°~70° C	-25°~70° C	-25°~70° C
Operating Humidity	0~95%	0~95%	0~95%	0~95%
Dimensions	76 x 45 x 27 mm	55 x 45 x 27 mm	76 x 76 x 27 mm	76 x 76 x 27 mm

TRANSMITTER RECEIVER COMBINATION FOR OPTIMAL PERFORMANCE	TRANSMITTER	RECEIVER	DISTANCE
	QT-TXRX-P	QT-TXRX-P	250m
	QT-TX-P	QT-RX-A	800m
	QT-TX-A	QT-RX-A	1500m

*POWER SUPPLIES NOT INCLUDED, ARE SOLD UPON REQUEST