



○ **Image Sensor**

○ **Effective Pixels**

○ **Signal System**

○ **Resolution**

○ **Sensitivity**

○ **Sensing Area**

○ **Lens**

○ **Auto Iris Lens**

○ **BackLight Compensation**

○ **Auto Gain Control**

○ **S/N Ratio**

○ **Electronic Shutter**

○ **White Balance**

○ **Video Output**

○ **Voltage**

○ **Power Consumption**

○ **Dimensions**

○ **Operation Temperature**

○ **Special Note**

○ **Warranty**

1/3" SONY Ex View CCD

NTSC: 510(H) X 492(V) • PAL:500(H) X 582(V)

NTSC

420 TVL

0.01Lux/F1.2

4.9mm x 3.7mm

CS/C Mount (With adapter option)

Video/DC Drive

ON/OFF Switchable

ON/OFF Switchable

More than 48dB (AGC OFF)

Auto:1/50 (1/60) ~ 1/100,000 sec

Manual:1/50 (60), 1/100(120), 1/250,1/500,1/1000, 1/2000, 1/4000, 1/10000 (S)

Auto Tracking White Balance

1V p-p 75Ω (BNC)

12VDC / 24VAC

~ 3W

68mm(W) x 46mm(H) x 115mm(L)

-10° ~ 50°C

Lens and Power Supply sold separately

18 Months