

oQ-610-PoE

Mini Domes



Features

FREE NVR SOFTWARE INCLUDED FOR LIVE VIEWING / RECORDING, E-MAP, ALARMS, PLAYBACK, BACKUP AND MORE. NO LICENSE REQUIRED. MANAGES UP TO 250 OPENQ DEVICES. REMOTE ACCESS VIA INTERNET EXPLORER

CONTROL YOUR oQ-610/P oE FROM INTERNET.

FULL CONTROL THROUGH THE **openQ** PRO SURVEILLANCE SYSTEM SOFTWARE INCLUDED WITH THE MINIDOME.

INCREDIBLE AND USEFUL CAPABILITIES LIKE POWER OVER ETHERNET (PoE), H.264 COMPRESSION METHOD.

FEATURING POWER OVER ETHERNET (POE)

Quaddrix is proud to introduce a new line of PoE (Power Over Ethernet) Mini Domes; ideal for high complexity installations, maximizing your budget allowance

Supports D1 Resolution, frame up to 30 FPS

Get over your image details and features, under unstable or variable lighting conditions.

0Q-610-PoE



Mini Domes



Technical Especification

Quaddrix[®]
Mini Domes

o Operation System	Embedded Linux
o Video Compression	H.264
o Audio Compression	G.711 PCM
o Alarm Input	2
o Alarm Output	1
o Record Resolution	VGA/QVGA/CIF/QCIF/D1
o Video Frame	PAL:25 FPS / NTSC:30 FPS
o Motion Detect	Yes
o DDNS Support	Yes
o Local Record	Support SD flash card
o Parallel Connection	Max 10 users parallel connection
o Network	10/100Mbps
o Event Manage	Email, FTP
o Web Server	Yes
o Client Software	1/4/6/8/9/16/25 video windows on 1 screen
o Pick-Up Device	1/3" SONY SUPER HAD CCD
o Effective Pixel	PAL:510 (H)*492 (V) NTSC 500 (H)*582(V)
o System	PAL/NTSC
o Resolution	420 TVL
o Minimum Illumination	Color: 0.5Lux/F1.2
o Electronic Shutter	1/60(1/50)~1/1000000 sec
o Power Supply	DC12V
o Lens	C/CS Lens
o Operation Temp.	-10°C ~ 50°C
o Dimension	Height: 100 mm Diameter: 130 mm



0Q-610-PoE Mini Domes



Technical Specification

NETWORK SPECIFICATIONS

AUDIO

○ Audio Compression	G.711/AMR
○ Cross Talking	Yes
○ Audio Input	1 CH Stereo Jack (for microphone)
○ Audio Output	1 CH Stereo Jack

GENERAL

○ Built In Web Browser	Yes
○ Internal Storage	Yes (Up to 1Gb fo local storage)
○ Security	Multiple user access levels with password protection
○ Users	UP to 10 users real time monitoring (account reusables)
○ WiFi	Yes Optional
○ Alarm Input	2 Channels
○ Alarm Output	1 Channel
○ Network Interfaces	1 CH RJ-45 10M/100M self-adaptive Ethernet 1 802.11b/g WiFi (optional)
○ Interface Connectors	1 RJ-45 1 Alarm socket 1 Mic IN 1 Audio Out 1 12VDC Jack
○ Network Protocols	UDP/IP, TCP/IP,DNS,PPPoE,DDNS

VIDEO

○ Signal System	PAL/NTSC
○ Output	1 CH RJ45 Network Connector
○ Video Compression	H.264
○ Encode Speed	NTSC: 1~30Fps adjustable PAL: 1~25Fps adjustable
○ Encode Resolution	D1, CIF, QCIF
○ Video Quality	1~6 (1 lowest, 6 highest)

Quaddrix[®]
Mini Domes